



DESCRIPTION

DURASEAL BITUM PRIME S is a solvent based free low viscosity bitumen primer, black in colour.

USES

DURASEAL BITUM PRIME S is used as bonding agent, primer and waterproofing coating on nearly all surfaces where afterward a bitumen coating system must be applied. Only used outside. To protect foundations against soil, corrosion, pillars and support walls against the aggressiveness of soil.

ADVANTAGES:

- One component
- No mixing required
- Chemical resistant
- Waterproofing layer
- Low viscosity
- Perfect bonding to the surface
- Dust binding

TECHNICAL SPECIFICATIONS:

Base	bitumen, additives
Color	black
Processing temperature	5°C up to + 30°C
Consistency	liquid
Density	approx. 1.02 g/cm ³
Curing time	approx. 3 hour (Depend of temperature, humidity, thickness and surface)
Consumption	approx. 0.2 – 0.3 kg/m ² (Depend of required protection)

APPLICATION

SURFACE PREPARATION

The surface must be dry or light humid, sound, absorbent and clean. Bonding inhibiting agents such as grease, oil, formwork oil and all loose particles and dust must be removed before application Duraseal Bitum Primer. Damaged area like cracks, holes or cavities have to be reprofiled with Drylex mortars.

APPLICATION

The application can be done crosswise in one step by brush, roller or spraying device. Tools with fresh not cured material, can be cleaned with solvents. Wash your hands after contact.

SHELF LIFE

24 MONTHS (FROST-FREE AND DRY, +5°C UP TO +25°C IN ORIGINAL PACKAGING).

PACKAGING

20 KG PAIL