

## DESCRIPTION:

DRYLEX MULTI POWER is a pvc base acrilate and ready to use adhesive, designed for the installation of vinyl and carpet flooring onto a variety of substrates.

## TYPICAL USES:

DRYLEX MULTI POWER can be used on concrete, cement renders, screeds, fibrous cement sheeting and timber. Suitable for use in interior floor applications in a domestic and commercial environment.

## ADVANTAGES:

- High initial grab
- Non-flammable
- Eco-friendly
- Mould resistant
- Can be use on floor and wall for vinyl and carpet tiles



## TECHNICAL DATA

Raw material base	Pvc Based Acrylate Dispersion
Solid content	%75
Airing time	Approx. 5-20 minutes on absorbent subfloors, approx. 30-40 minutes on non-absorbent subfloors
Open time	Approx. 30-50 minutes
Cleaning agent	Water, before adhesive starts to dry
Storage time	24 months at room temperature
Storage temperature	Not below +5 °C, sensitive to frost

## YIELD

FLOOR COVERING	TROWEL SIZE	COVERAGE
Vinyl And Carpet Tiles	1.6 mm V notch trowe	5 m <sup>2</sup> pe

## PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding. New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations. All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking. DRYLEX MULTI POWER, floor levellers and plasters must be allowed to cure. It is recommended to prime the surface with a DRYLEX bonding agent before the application of DRYLEX MULTI POWER.



**MIXING:**

No mixing required.

**APPLICATION:**

1. Stir before use.
2. Spread the adhesive on the substrate with a V notched trowel. The adhesive must be tacky before the vinyl is placed onto the substrate. To check if the adhesive is tacky, place a small piece of vinyl onto the adhesive, and then pull away. If there are visible strings of adhesive, then the adhesive is tacky.

**DRYING & CURING:**

Once the vinyl has been laid, they must not be trafficked upon or disturbed for a minimum of 24 hours at 20°C. If application is over a non-porous substrate, allow for a minimum of 48 hours at 20°C. Note that the cure time will be delayed if the temperature is below 20°C and/or there is insufficient air circulation.

**CLEANING:**

Clean tools with water immediately after use.

**STORAGE & SHELF LIFE:**

Up to 24 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity

**LIMITATIONS:**

Not suitable for exterior use. Not suitable for use in water immersion applications i.e. showers, baths, swimming pools and spas etc. If your project requires Building Consent, please email info@ agelchemicals.de about the suitability of this product before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**HAZARD STATEMENTS:**

Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

**SAFETY INSTRUCTIONS:**

Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing mist/ vapours/spray. Contaminated work clothing should not be allowed out of the workplace.

**RESPONSE:**

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Take off contaminated clothing and wash before reuse. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention